

## Features

- ✓ Air velocity measurement: m/s, km/hr, ft/min, MPH, Knots & build in temperature °C/°F , humidity %RH
- ✓ Air velocity compensation in atmospheric pressure
- ✓ Air flow measure: CMM, CFM
- ✓ Telescoping hot wire probe
- ✓ Fast response
- ✓ Large LCD display with backlight
- ✓ Min/Max/Avg & 2/3Vmax function
- ✓ With USB Interface supply power
- ✓ Adjustable auto power off timer
- ✓ Data Hold Function
- ✓ Battery Life indicator
- ✓ Tilt Stand



## Specifications

<b>Measurement Range</b>	Air Velocity: 0 ~ 25 m/s (0 ~ 6000ft/min)
	Air flow: 0 ~ 999900 m <sup>3</sup> /min (ft <sup>3</sup> /min)
	Temperature: -20°C ~ 60°C (-4°F ~ 140°F )
	Humidity: 0 ~ 100% RH
<b>Accuracy</b>	Air Velocity/Flow: ±3% reading ±1% F.S.
	Temperature: ±0.8°C (±1.5°F )
	Humidity: ±3.5% RH
<b>Resolution</b>	Air Velocity: 0.01m/s (1 ft/min)
	Air flow: 0.001 m <sup>3</sup> /min (ft <sup>3</sup> /min)
	Temperature: 0.1°C (0.1°F )
	Humidity: 0.1% RH
<b>Sampling Rate</b>	2 time/sec
<b>Telescopic Probe Length</b>	330 to 870 mm (4 sections)
<b>Cable Length</b>	1890 mm
<b>Max. Extension Length</b>	2220 mm
<b>Power Source</b>	9V alkaline battery
<b>Operatoin Condition</b>	0 ~ 50°C (<80%RH)
<b>Storage Condition</b>	-10 ~ 60°C (<70%RH)
<b>Dimensions</b>	185(L) x 65(W) x 36(H) mm (meter only)
<b>Weight</b>	Approx. 410g
<b>Accessories</b>	Battery, Instruction Manual, Carrying case