

## Features

- ✓ Interchangeable Digital Probes
- ✓ Thermistor Sensor For Temperature Measurement, Fast Response Time
- ✓ Dual Display
- ✓ Dew Point Measurement
- ✓ PC Interface
- ✓ 16,000 Records Data Logger
- ✓ Auto Shut Off For Battery Saving
- ✓ Extending Cable Available
- ✓ Tilt Stand

## General Specifications

<b>Sensor</b>	Electronic capacitance polymer film sensor/NTC
<b>Range</b>	Temperature: -20 ~ 60°C ; -4 ~ 140F Humidity: 0 ~ 100%RH
<b>Accuracy</b>	±0.8°C, 1.5°F ±2.0%RH
<b>Resolution</b>	0.1°C ; 0.1°F ; 0.1%RH
<b>Response Time (@t90)</b>	Humidity: 60 sec. ; Temperature: 10 sec
<b>Operation Temp</b>	0°C ~ 40°C (<80%RH)
<b>Storage Temp</b>	-10°C ~ 60°C (<70%RH)
<b>Parameters Displayed</b>	Relative humidity, temperature and dew point
<b>Battery</b>	9V battery
<b>Dimensions</b>	185x65x36 mm ; Probe: 94x15mm Dia
<b>Weight</b>	Approx.285g
<b>Accessories</b>	9V Battery, Instruction Manual, Windows software, USB cable, RS-232 Cable (Option), Carry Case, AC Adapter (Option)

