

Features

- ✓ Simple One-Handed operation
- ✓ Laser Targeting
- ✓ LCD With Back Light
- ✓ °C/°F Select switch
- ✓ Laser ON/OFF switch
- ✓ Automatic Power off
- ✓ Display Hold function



General Specifications

Parameter	TI 300	TI 302
Display	3 1/2 digit LCD	3 1/2 digit LCD
Low Battery	Symbol will appear when the battery is low	Symbol will appear when the battery is low
Measurement Range	-20°C ~ 500°C / -4°F ~ 932°F	-20°C ~ 500°C / -4°F ~ 932°F
Accuracy	±2% or ±2°C(3°F)	±2% or ±2°C(3°F)
Resolution	0.5°C ; 0.5°F	0.1°C ; 0.2°F
Distance to Spot(D:S)	8:1	12:1
Response Time	500m Sec.	500m Sec.
Emissivity	Pre-Set at 0.98	Pre-Set at 0.98
Battery Type	9V Battery	9V Battery
Operating Temperature	0°C to 40°C (< 80% humidity)	0°C to 40°C (< 80% humidity)
Storage Temperature	-10°C to 60°C (< 70% humidity)	-10°C to 60°C (< 70% humidity)
Dimension	157.5mm×115mm×36mm	157.5mm×115mm×36mm
Weight	Approx. 200g	Approx. 200g
Accessory	Manual, 9V battery, Carrying case	Manual, 9V battery, Carrying case