

Features

- ✓ Slim and Light weight size
- ✓ True RMS measurement
- ✓ Measuring Current : AC 1000A
- ✓ Data Hold function
- ✓ MinMax function
- ✓ Auto Power Off
- ✓ Autoranging

General Specifications

Numerical Display	4 digital liquid crystal(LCD), Maximum reading 6000
Low Battery Indication	
Sampling Rate	2 Times/sec
Power Source	CR2032(3VDC) battery x 1
Auto Power Off	10 minutes
Operating Temperature and Humidity	0°C to 40°C(32°F to 104°F); < 80%RH
Storage Temperature and Humidity	-10°C to 60°C(14°F to 140°F); < 70%RH
Jaw Opening Diameter	40 mm
Dimensions	207(L)×66(W)×26(H)mm
Weight	Approx. 153 grams
Accessories	Carrying Case, Batteries, Test Lead, Instruction Manual



Electrical Specifications

Parameter	Specification	
ACA	Range	600A/1000A
	Resolution	0.1A/1A
	Accuracy	±1.9% ± 5dgts
ACV	Range	6V/60V/600V
	Resolution	0.001V/0.01V/0.1V
	Accuracy	±1.2% ± 5dgts
DCV	Range	6V/60V/600V
	Resolution	0.001V/0.01V/0.1V
	Accuracy	±1% ± 2dgts
Ohms	Range	600Ω/6KΩ/60KΩ/600KΩ
	Resolution	0.1Ω/0.001 KΩ/0.01KΩ/0.1KΩ
	Accuracy	±1% ± 2dgts