

Features

- ✓ 4 Digital display
- ✓ 10 μ A resolution
- ✓ Autoranging
- ✓ Auto Zero
- ✓ Auto Power Off
- ✓ Max Hold function
- ✓ Data Hold function

General Specifications

Jaw opening size	28mm
Battery	1.5V AAA x 2
Dimensions / Weight	218 x 64 x 30mm / 270g
Accessories	Battery, test lead, instruction manual, carrying case



LED Back light

General Specifications

Parameter	Specification	
AC Current (Autorange)	Range	10A/80A/100A
	Resolution	1mA/10mA
	Accuracy	1.2%rdg \pm 5dgts(50~60Hz); 2.5%rdg \pm 5dgts(50~1KHz)
	Overload Protection	150Arms
AC mA Current (Autorange)	Range	60mA/600mA
	Resolution	10 μ A/100 μ A
	Accuracy	1.2%rdg \pm 5dgts(50~60Hz); 2.5%rdg \pm 5dgts(50~1KHz)
	Overload Protection	150Arms
DC Voltage	Range	600V
	Resolution	0.1V
	Accuracy	\pm 1%rdg+2dgts
	Overload Protection	660Vrms
AC Voltage	Range	600V
	Resolution	0.1V
	Accuracy	\pm 1.5%rdg+5dgts
	Overload Protection	660Vrms
Resistance (Ohms)	Range	1000 Ω
	Resolution	0.1 Ω
	Accuracy	\pm 1%rdg+2dgts
	Overload Protection	660Vrms
Frequency Hz (A)	Range	0/100Hz/1KHz
	Resolution	0.1Hz/1Hz
	Accuracy	0.5rdg% \pm 2dgts
	Sensitivity	10mArms min
Frequency Hz (V)	Range	0/100Hz/1KHz
	Resolution	0.1Hz/1Hz
	Accuracy	0.5% \pm 2dgts
	Sensitivity	5Vrms min
Continuity	Range	··))
	Active Region	<35 Ohm
	MAX Test Voltage	-3.3VDC
	Overload Protection	600Vrms