

## Features

- ✓ 6,000 Count Digital large scale display
- ✓ Analog Bar graph
- ✓ AC 100.0 Amps capability
- ✓ AC 0.001mA resolution
- ✓ True RMS reading
- ✓ Auto Ranging
- ✓ Auto Hold
- ✓ Data Hold
- ✓ Peak Hold
- ✓ Comparator
- ✓ Low Pass Filter with high stability
- ✓ Auto Power Off (Disable)
- ✓ Up to 40mm dia. (750MCM) Conductor Size
- ✓ 4 feet Drop Proof
- ✓ Deluxe Carrying Case
- ✓ Hand Guard & Stream Line Designed
- ✓ Convenient Battery Door



## Specifications: (All at 23°C±5°C, ≤ 80% R.H.)

Parameter	Specification	
ACA	Ranges	6.000mA/60.00mA/600mA/6A/60A/100A
	Resolution	0.001mA
	Basic Accuracy	±(1.0%+3d)

## General Specifications

Sampling Rate	5 times/sec
Overload Indication	"OL"
Low Battery Indication	
Auto Power Off	Approx. 20 minutes
Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Temperature Coefficient	0.2 x (Spec. Accuracy)/ °C, <18°C, >28°C
Maximum Conductor Size	Up to 40 mm dia. (750MCM) Conductor size
Maximum Jaw Opening	Up to 43mm
Safety: IEC 61010 and designed to meet UL61010 specifications	CAT III 300V
Power Requirement	1.5V x 2pcs AAA Size batteries (IEC LR03)
Battery Life	60 In hours (Alkaline battery)
Size	78mm(W) x 203mm(L) x 42mm(D)
Weight	300 In grams
Accessories	Carrying Case, Alkaline battery (installed) and manual